

NOTES:

1. MAY BE REDUCED UPON APPROVAL OF THE ENGINEER. REFER TO SECTION 3-06.
 2. FOR ACCESS ROADS SERVING 90 ADT OR LESS AND HAVING NO POTENTIAL FOR CONNECTIVITY, THE NEED FOR A WIDENED SHOULDER FOR A WALKWAY WILL BE EVALUATED ON A CASE BY CASE BASIS.
 3. AN 8 FT PAVED SHOULDER OR A 5-FOOT SEPARATED WALKWAY IS REQUIRED ON ONE SIDE IF ADT IS 250 OR GREATER, OR IF SAFE WALKING CONDITIONS FOR STUDENTS ARE IMPOSED PURSUANT TO RCW 58.17.060, 58.17.110 OR APPLICABLE COUNTY CODES.
 4. EASEMENT WIDTH VARIES, BUT SHALL BE NO LESS THAN 30 FEET.
- SEE TEXT CHAPTER 3

PUBLIC ROAD STANDARD – RURAL

ROAD CLASSIFICATION	DESIGN SPEED (MPH)	PAVEMENT WIDTH	TRAVEL LANES	WALKWAY WIDTH	R/W WIDTH	SEE STD DRAWING
LOCAL ACCESS ROAD (ADT < 250)	25 (1)	22'	2x11'	5' MIN SEPARATED	42'-50'	3-040
SUBCOLLECTOR (ADT 250 – 2000)	25	22'	2x11'		42'-60'	3-040
COLLECTOR (ADT 2001 – 3000)	30 (1)	30'	2x15'		50'-60'	3-040

PRIVATE ROAD STANDARD – RURAL

ROAD CLASSIFICATION	DESIGN SPEED (MPH)	PAVEMENT WIDTH	SURFACE	EASEMENT WIDTH	WALKWAY SHOULDERS	SEE STD DRAWING
PRIVATE LOW VOLUME ACCESS (90 ADT OR LESS)	20	20'	GRAVEL	(4)	NONE	3-080
PRIVATE SUBCOLLECTOR (91 TO 1000 ADT)	25	22'	PAVED	(4)	(3)	3-090

SNOHOMISH COUNTY PUBLIC WORKS

APPROVED BY:

3-060 ROAD STANDARDS – NON-ARTERIALS (RURAL)

COUNTY ROAD ENGINEER

DATE

